

Estimate / Order Cover Page

Date: ____/____/____

From:

Fax to Special-Lite, Inc.: (800) 423-7610

Pages including this one: _____

Estimate

Purchase Order: Your PO#: _____ Signature: _____

- This job was estimated by Special-Lite. Please provide E#: _____
 This job was estimated with the Satellite estimating program. Include Satellite estimate with P.O.
 This job was estimated with the field price book

Special-Lite to provide Submission Drawings at additional cost

Contact: _____

Company: _____ Email: _____

Phone #: _____ Fax #: _____

Bill To: _____ Cell #: _____

Ship To: _____

Use Ship To address on file with S-L

Freight:

- Prepaid and added to invoice (Default)
 Collect (not available if shipped to job site)
 Third Party (bill to address on file with S-L)
 Customer Pickup

All Product is shipped
F.O.B. Decatur, MI

Please indicate when material is needed.

Date required for shipment: ____/____/____

Job Name: _____ Job Location Address: _____

Job Site Telephone #: _____

Job Site Contact Name: _____

Owner: _____

Architect: _____

Special-Lite EXPRESS SL-17 User's Guide

Please review the following instructions before filling out the Express SL-17 order form. To avoid errors or delays, please make sure that every section has one selection marked.

NOTE: All Express orders are shipped within two weeks of our receipt of signed priced order acknowledgment and approved payment terms. Orders requiring shop drawings are not part of this program.

The numbers of this step-by-step guide correspond to the sections on the order form.

Please make sure all customer information is filled in correctly and completely. Make sure that you have included your customer PO number or credit card information. If your order is shipping to the jobsite, we need the job site phone number and job site contact.

- 1 **Quantity of Single Doors or Pairs of Doors:** All doors on each sheet must be identical. Use separate sheets for different doors.
- 2 **Door Opening Width and Height:** Door opening height is measured from finished floor. Door opening width is measured from inside jamb to inside jamb. All doors will have a 3/4" bottom undercut. Maximum door size is 48" x 96". Minimum door size width is 30".
- 3 **Aluminum Finish:** Aluminum finish will apply to perimeter of door, vision lite kits, perimeter frames, hinges, flush bolts and recessed pulls.
- 4 **FRP Facesheet Color:** Choose from nine standard SpecLite3[®] FRP colors or six classic colors (white, black, red, dark grey, blue and green). Check appropriate box to indicate interior or exterior side of door.
- 5 **Vision Lite:** Special-Lite Standard Half-glass and Narrow lite sizes vary according to the door size and hardware.
- 6 **Glass:** Glass will be furnished in 1/4" or 1" clear tempered only. Glass may also be furnished by others.
- 7 **Hinge:** SL-11HD continuous hinges will be provided in the finish selected in section 3. If you choose one of the other hinge sizing options, you will be responsible for field preps and reinforcements.
- 8 **Locking Hardware:** All lockset preps will be located to match a strike location of 40-5/16" centerline from floor. We will provide a 4-7/8" lock strike prep on frame for single doors and in the inactive leaf of a pair of doors.
- 9 **Flush Bolts/Surface Bolts:** This section pertains to a pair of doors with an inactive leaf.
- 10 **Push/Pull:** If a Flush pull is selected, the aluminum finish will match the finish that was chosen in section 3. Pull centerline is located 35" from finished floor and inboard to allow for future hardware attachment.
- 11 **Perimeter Frame:** To determine the frame size for a **tube frame**, add frame face dimensions to each side of the door opening. For instance, with a door opening width of 36" and a frame face of 2", the overall frame size width will be 40". For the frame size height, add the door opening height to the frame face of the header to determine this measurement. Remember, all doors will have a 3/4" bottom undercut. For **insert frames**, provide existing door opening measurements. Door Opening Height must be measured from finished floor. Insert frames must be used with a concealed continuous hinge (the SL-11HD continuous hinge is recommended).
- 12 **Transom Frame:** All transom frames will be fabricated to 10' – 6" in height with applied glass stops. The transom vertical pieces are to be cut to size in the field. The transom will be open for 1/4" or 1" glass. Please indicate glass thickness.
- 13 **Threshold:** Our standard threshold size is 1/2" x 5". All thresholds will be fabricated to fit from jamb to jamb. Threshold clips will be supplied with all thresholds to ease installation.

Please make sure to review your completed form for accuracy. For doors or frames that do not qualify as Special-Lite Express SL-17 orders, please use our regular order forms, or contact our Order Processing Department at (800) 821-6531.

Additional Notes:

- All doors are reinforced for surface applied closers.
- All doors will have a 3/4" bottom undercut.
- All lockset preps will be located to match a strike location of 40-5/16" centerline from floor.

SPECIAL-LITE **Express SL-17** Order Form

Phone: (800) 821-6531 Fax: (800) 423-7610

Date: ___/___/___ Company: _____ Contact (printed): _____

Telephone #: _____ Fax #: _____

Bill To: _____ Ship To: _____

Freight:
 Collect (not available if shipped to jobsite)
 Prepaid and added to invoice
 Third Party (bill to address on file with S-L)

All Product is shipped
 F.O.B. Decatur, MI

Use Bill To address on file with S-L Use Ship To address on file with S-L


Preferred Method of Payment:

Open Account (Pending credit approval) Your PO#: _____ Signature: _____

Visa **MasterCard**
 Card #: _____ Exp. Date: ___/___ Signature: _____


Job Name: _____ Job Site Tel. #: _____ Job Site Contact: _____

1a. Quantity of Single Doors: _____



-OR-

1b. Quantity of Pairs of Doors: _____



All doors on this sheet must be identical. Use separate sheets for different doors.

Enter a door mark for the doors on this sheet below.
Door Mark (I.D.):

2. Door Opening Width (inches): _____ **Height:** _____
 Single doors maximum D.O.: 48" x 96"
 Pairs of doors maximum D.O.: 96" x 96"
 Minimum door width is 30"

3. Aluminum Finish: (check one)
 Clear Dark Bronze
Int. Classic Color: _____

Ext. _____

4. FRP Facesheet Color: (check one)

Int.	Ext.	Int.	Ext.	Int.	Ext.
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Beige	Light Grey	Sandstone	Boysenberry	Dark Bronze	Seawolf
Hartford Green	Military Blue	Slate Grey			

5. Vision Lite: (check one)
 12" x 12" Half glass (22" x 32" max.)
 Narrow lite (6" x 32" max.) No vision lite

6. Glass: (check one)
 1/4" Clear tempered by S-L 1/4" by others
 1" Clear tempered by S-L 1" by others
 No Vision Lite/Not Applicable

7. Hinge: (check one)
 SL-11HD furnished and installed (recommended)
 Sized for 3/8" hinge clearance (requires field prep)
 Sized for 1/8" hinge clearance (requires field prep)

8. Locking Hardware: (check one)
 Mortise lock pocket prep Surface vertical rod reinforcement
 Cylindrical lock prep Rim exit / Push/Pull reinforcement

9. Flush Bolts / Surface Bolts: (check one)
 Flush bolts furnished and installed
 Prepped for flush bolts - ANSI 1" x 6-3/4"
 Reinforce for surface bolts
 No flush bolt / surface bolt prep or installation

10. Recessed Pull: (check one)
 SL-82 SL-86 No Recessed Pull

11. Perimeter Frame: (check one)

<input type="checkbox"/> 2" x 4"	<input type="checkbox"/> 1-3/4" x 4"	<input type="checkbox"/> 5/8" x 4-1/2"
<input type="checkbox"/> 2" x 4-1/2"	<input type="checkbox"/> 1-3/4" x 4-1/2"	<input type="checkbox"/> 1" x 4-1/2"
<input type="checkbox"/> 2" x 5"	<input type="checkbox"/> 1-3/4" x 5"	<input type="checkbox"/> 1" x 6"
<input type="checkbox"/> 2" x 6"	<input type="checkbox"/> 1-3/4" x 6"	<input type="checkbox"/> 1030 Insert Frame
		<input type="checkbox"/> No frame

12. Transom frame: (check one)
 No Transom Open for 1/4" glass Open for 1" glass

13. Threshold by Special-Lite: (check one)
 None 1/2" x 5" flat threshold

Fax to: (800) 423-7610 Thank You!