





# SL-16 Door & Frame Estimate/Order Form

**Door(s) & Frame(s)**  
  **Door(s) only**  
  **Frame(s) only**

**1. Door Mark (I.D.):** \_\_\_\_\_ **Building Type:** \_\_\_\_\_

**2. Handing:**  Single    Pairs    Unequal Pair

(Specify quantity of single/pairs of doors required. All doors on each sheet must be identical. Use separate sheets for doors with differences.)



**3. Opening Dimensions:**

(Measure opening to finished floor. For both width and height, measure opening at several points and record the smallest dimension.)

Width: \_\_\_\_\_ Height: \_\_\_\_\_ Thres. Height: \_\_\_\_\_ (default bottom undercut: 3/4")

Rough Opening (masonry to masonry)  
  Door Opening (jamb to jamb)  
  Net Door Size  
  Net Frame Size (outside tip to tip of new frame)

**4. Swing:** Degree of Door Opening \_\_\_\_\_°

**5. Aluminum Finish:** (Special anodizing or painting will result in additional lead time. Finish selected here will apply to doors, frames and aluminum vision kits.)

Clear (stock)  
  Dark Bronze (stock)  
  Black  
  Champagne  
  Light Bronze  
 Medium Bronze  
 Painted: (enter code) \_\_\_\_\_

**6. Aluminum Facesheet:**   Ext Int 3/4 Embossed     Ext Int Smooth     Ext Int Fluted

\*If needed please clarify with sketch/detail and/or further instruction at end of form.

**7. Vision Lite:**  Yes  No **FL Series is standard.** Options:  FL-LPBev Lite Kit    FL-SecureLite (1/2" glass)

12" x 12"  
  Half Lite  
  Full Lite  
  Narrow Lite  
 Double Lite  
 Aluminum Surface Muntins\* (1/2" or 1-1/4" width)  
 Other\* (provide sketch)

**8. Glass/Louvers:**  By Special-Lite    By Others    None \*If needed please clarify with sketch/detail and/or further instruction at end of form.

1/4" Polycarbonate  
  1/4" Tempered (Clear)  
  1/4" Laminated (Clear)  
  1" Tempered (Clear)  
  Other\* (provide thickness & detail)  
 Louver  
 Louver with screen  
 1" Panel (specify face sheet)  
 1/4" Panel (specify face sheet)  
 1" w/Internal Muntins\*

**9. Framing:**  By Special-Lite    By Others    No Framing Unless specified, existing door stop is assumed to be 5/8" high.

**Frames Options:**  Perimeter    Complicated

Provide any existing hardware locations to match. Please include a separate elevation for any frame more complicated than a perimeter frame.

**Frame Glass Thickness:**  1/4"    1"

Provide glass thickness for transom/side lite. Glass not supplied by Special-Lite for framing.

**9. Framing (continued):**

**Door Mark (I.D.):** \_\_\_\_\_

**Frame Panels:**

By Special-Lite       By Others

1/4"       1"       1-3/4"

**Heavy Wall Tube Frames with Applied Stop :**

<input type="checkbox"/> 2" x 4"	<input type="checkbox"/> 5/8" x 4-1/2"	<input type="checkbox"/> 1" x 4-1/2"	<input type="checkbox"/> 1" x 6"
<input type="checkbox"/> 1-3/4" x 4"	<input type="checkbox"/> 2" x 4-1/2"	<input type="checkbox"/> 2" x 5"	<input type="checkbox"/> 2" x 6"
	<input type="checkbox"/> 1-3/4" x 4-1/2"	<input type="checkbox"/> 1-3/4 x 5"	<input type="checkbox"/> 1-3/4" x 6"

**Thermally Broken Frames:**

2" x 4-1/2"       2" x 6"

**Heavy Wall Flush Glazed Frames:**

<input type="checkbox"/> 1-3/4" x 4-1/2" <small>Non-Therm Improved</small>	<input type="checkbox"/> 2" x 4-1/2" <small>Thermally Improved</small>	<input type="checkbox"/> 2" x 6" <small>Thermally Improved</small>
---	---	---

**Retrofit Framing :**

Insert Frame       Insert Frame & Capping       Capping (Frame Detail Required)

**10. Continuous Hinge by Special-Lite:** (SL-11HD)  Yes  No

**11. Adjustable Bottom Brush by Special-Lite:** (SL-301)  Yes  No

**12. Adjustable Astragal by Special-Lite:** (AS-4A) with optional radius meeting stile  Yes  No

**13. Hardware:** (Surface closers and surface holder/stops are field prepped and installed. The default strike centerline is 40 - 5/16" from floor.)

Quantity	Manufacturer	Item#	Size	Finish	Supplied by SL	Prep per Temp.	Will be Sent to SL
					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

**14. Special Instructions:** (If your order has specific performance requirements to meet, please note it here.)