







SPECIAL-LITE, INC. **Express SL-17/20** Order Form

Phone: (800) 821-6531 **Fax:** (800) 423-7610

Date: _____	Company: _____	Contact: _____
Telephone #: _____	Fax #: _____	
Bill To: _____ _____ _____	Ship To: _____ _____ _____	Freight: Collect (not available if shipped to jobsite) Prepaid and added to invoice Third Party (bill to address on file with S-L) <small>All Product is shipped F.O.B. Decatur, MI</small>
Use Bill To address on file with S-L	Use Ship To address on file with S-L	

Preferred Method of Payment: Open Account (Pending credit approval)			Your PO# _____	Signature: _____
Job Name: _____	Job Site Tel. #: _____	Job Site Contact: _____		

1a. Single Doors: <div style="text-align: center; font-size: 2em; font-weight: bold; margin: 10px 0;">-OR-</div> <div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> LH  Quantity: _____ </div> <div style="text-align: center;"> RH  Quantity: _____ </div> </div> <div style="display: flex; justify-content: space-around; margin-top: 10px;"> <div style="text-align: center;"> LHRB  Quantity: _____ </div> <div style="text-align: center;"> RHRB  Quantity: _____ </div> </div>	1b. Pairs of Doors: <div style="text-align: center; margin: 10px 0;">  (check active leaf) Quantity: _____ </div> <div style="text-align: center; margin-top: 10px;">  Quantity: _____ </div>	<p>All doors on this sheet must be identical. Use separate sheets for different doors.</p> <p>Enter a door mark for the doors on this sheet below.</p> <p>Door Mark (I.D.): _____</p>
--	--	---

2. Door Opening Width (inches): Single doors maximum D.O.: 48" x 96" Pairs of doors maximum D.O.: 96" x 96" Minimum door width is 30"	Height: SL-301 comes standard with all Express Doors
---	---

3. Alum. Finish: (check one) Clear Dark Bronze

4. FRP Face Sheet: SpecLite 3® Sandstone-Textured
Interior FRP:
Exterior FRP:

5. Vision Lite: (check one) 12" x 12" Narrow Lite (6" x 32" max.)	 Half glass (22" x 32" max.) No vision lite
--	---

6. Glass: (check one) 1/4" Clear tempered by S-L	 No Vision Lite/Not Applicable 1/4" by others 1" by others
--	---

7. Hinge: (check one) SL-11HD furnished and installed (recommended) Sized for 3/8" hinge clearances (requires field prep) Sized for 1/8" hinge clearances (requires field prep)

8. Locking Hardware: (check one) Mortise lock pocket prep Surface vertical rod reinforcement Cylindrical lock prep Rim exit / Push/Pull reinforcement
--

9. Flush Bolts/Surface Bolts: (check one) Flush bolts furnished and installed Prepped for flush bolts - ANSI 1" x 6-3/4" Reinforce for surface bolts No flush bolt/surface bolt prep or installation

10. Recessed Pull: (check as desired) SL-82 SL-86 No Recessed Pull
--

11. Perimeter Frame: (select from drop down menu) Yes No Frame

12. Transom frame: (check one) Yes No Transom Open for 1/4" glass Open for 1" glass
--

13. Threshold by Special-Lite: (check one) None 1/2" x 5" flat threshold

Email to: orders@special-lite.com Thank you!
