

SL-23 Fire-Rated Door Estimate/Order Form

	☐ Door(s) & Frame(s) Door(s) only	☐ Frame(s) only		
1.	Door Mark (I.D.):			Building Type:	
2.	Handing: Single	☐ Pairs	Unequal Pair	(Specify quantity of single/p sheet must be identical. Use	pairs of doors required. All doors on each separate sheets for doors with differences.)
		RH Quantity:	Quantity:	-	Height - measured from finished floor to
	LHRB Quantity:RH	RB Interior Quantity:	Quantity:	·	the underside of header
3.	Opening Dimension			Opening ← Width →	Threshold Opening Height Width
		Height:	Thres.	Height:	(default bottom undercut: 3/4")
4.	Swing: Degree of Door	Opening	o -		
5.	Edge Capping Finish	Stainless Steel			
6.	☐ ☐ Military Blue	Ext Int Beige Brick Red	Ext Int Hartford Green Seawolf	Ext Int Light Grey ☐ ☐ Sage Brown	Ext Int Dark Bronze
7.	Stainless Steel Visio	n Lite: ☐ Yes ☐ No ☐ 6" x 28"	□ 10" x 10"	☐ 20" × 28"	
8.	Glass: ☐ 3/16" FireLite Stand	, ,	By Others Other:	None	
9.	Fire-Rated Framing: Unless specified, existing door stop is as		☐ By Special-Lite	☐ By Others	☐ No Framing
		rame & Capping: ne detail for capping configuration.	☐ Dark Bronze	□ Black	☐ Clear
	☐ Hollow Metal	Frame: (primed only)			
10.	Label: (Check one)	☐ 30 minute	☐ 45 minute	☐ 60 minute	90 minute

Door Mark (I.D.):

11. Hardware: (Surface closers and surface holder/stops are field prepped and installed. The default strike centerline is 40-5/16" from floor.)

Quantity	Manufacturer	Item#	Size	Finish	Supplied by SL	Prep per Temp.	Will be Sent to SL

12.	Speci	ial I	Instructions:	(enter below)
-----	-------	-------	---------------	---------------

12	12. Special Instructions: (enter below)						