

# RESTROOM PARTITIONS

## Partitions, Privacy Screens & Stall Doors

Special-Lite Restroom Partitions leverage our proven design and superior materials used in our entrance systems. We created FRP restroom partitions that are just as durable, maintenance free and long lasting as our doors. Our partitions are the ideal choice for restroom facilities that are expected to endure heavy use and frequent abuse - such as K-12, higher education, athletic facilities, arenas, locker rooms, pools, showers, spas, retail, restaurant and host of other public facilities.



### Features

- Custom Fabricated
- Non-Corrosive Materials
- Tamper resistant fasteners
- colored-through FRP face sheets
- Extruded 1-Piece Aluminum pilaster shoes
- Unique ADA gravity hinge, self-closing, slide function
- 6063-T6 extruded aluminum alloy
- Meets NFPA 286 Standard
- Aluminum is Class 1, Clear Anodized
- Class A or Class C FRP Face sheet available
- Floor Mounted, overhead-braced configurations
- Panels are 1.25" thick
- Pilasters are 1.25" thick

### Benefits

- Perfect for Restroom Partitions, Shower Stalls, Private Changing Rooms
- Built to endure heavy use and abuse
- Great for use in corrosive environments
- FRP Face sheets are resistant to dents, scratches, stains
- FRP Face sheets cannot rust or rot
- Tough yet 20% lighter than steel system; 50% lighter than HDPE
- Peek Proff Stalls & Compartments
- ADA door stop allows for emergency access
- FRP face sheets have exceptional cleanability
- Limited 10 year Parts & Labor Warranty

### Colors

Aluminum Clear Anodized  
Standard .090" FRP Through-Colors

- Pearl Gray
- Beige
- Colonial White
- Black

Upgrade to .120" SpecLite3™ FRP face sheets

- See color chart for reference



## Standard Stall, ADA Stall or Ambulatory Stall

2 Pilasters, 1 Panel, 1 Door & Hinge, 2 Shoes, Headrail, Doorstop, Brackets, Hardware and all fasteners. When required will include strike, latch & pull.

## Urinal or Privacy Screen

48" height x 18" deep is standard. Other depths available. 46" tall through-bolted "T" shape brackets. All fasteners. Urinal or Privacy Screens have aluminum perimeter frame, .090" thick interior grade FRP face sheet as the standard, and closed cell foam core.

## Doors (Manufactured date and Production # etched on the bottom of doors.)

Standard Height is 58". Both 24" and 36" are standard door opening widths. Standard Stall typically in-swing doors. ADA and Ambulatory Stalls typically out-swing doors. Custom door width sizes available. Doors have aluminum perimeter frame, .090" thick interior grade FRP face sheet as the standard, and closed cell polyurethane foam core.

## Partition Panels

58" height x 59" deep is standard panel size. Custom size available up to 96" deep. Panels have aluminum perimeter frame, .090" thick interior grade FRP face sheet as the standard, and closed cell polyurethane foam core.

## Pilasters (Some layouts may offer no through-bolting on face of pilasters. Note on Estimate/Order form for this consideration.)

80" tall and available in a variety of width sizes from 3" - 12" in 1" increments. Also available in 14" - 24" in 2" increments. Larger custom sizes available up to 120", but FRP will have a seam at 84". Doors hinge and latch on the pilasters. Brackets through-bolt to the pilasters to hold divider panels. All pilasters have plastic mounting bolt in the bottom for easy height adjustment. 3" - 6" pilaster made with hollow aluminum extrusions and have FRP face. Pilasters over 6" wide have aluminum perimeter frame, .090" thick interior grade FRP face sheet as the standard, and closed cell foam core.

## Shoes

Clear anodized aluminum shoe is 4" tall.

## Headrail

Top extrusion that runs over the top of the pilasters. peaked top to discourage individuals from hanging on it. Has snap-in end plugs and wall brackets that may be necessary in some applications.

## Doorstop

Full length door stop screw applied to pilasters. (For ADA-compliant, outswing doors, the door stop is applied to the door.) Hollow bulb used.

## Hinges

Two full mortise aluminum continuous hinges available. SL-38 is standard hinge, used on standard stalls, non-self-closing. SL-64 is our gravity, self-positioning hinge and is supplied as standard on ADA or Ambulatory stalls. Option to upgrade to SL-64 hinge on a standard stall is available.

## Door Pull

All ADA doors and standard outswing stall doors only.

## Strike and Latch

Aluminum strike through-bolted to pilaster. Latch through-bolted to door.

## Hook Bumper

Hook bumper standard to be used as stop on inside of door. If outswing door, wall mounted bumper is standard.

## Brackets

56" 'U' shape bracket is standard. 'H' bracket available and standard for alcove partition designs. 46" 'T' shaped bracket used for urinal screens. Request a 56" 'T' bracket for mounting partitions to wall if you need additional strength or have existing holes that need to be covered.

## Fasteners

Fasteners for assembly are supplied. Through-bolts hold panels to brackets. Torx with a pin is used. Head is T25.

## Complimentary Tool Kit

The following tools are included with each partition order: Concrete drill bit, drill and tap for doorstop mounting and a T25 bit.

