

FIRE-RATED DOORS & FRAMES

The AF-FR Series All-Fiberglass doors are available with smooth, pebble grain, rustic wood grain, contemporary wood grain or sandstone-textured face sheets and in 20, 45, 60, and 90 minute fire ratings. Tested in accordance with UBC 7-2, NFPA 252 and UL 10C requirements, the AF-FR Series have passed the 1-1/2 hour positive pressure test, hose stream test, and 250 degree temperature rise tests, and are labeled by Intertek.

Features & Benefits

- Identical in appearance to AF Composite series doors, with a wide variety of finish and texture options and smooth door edges.
- Smooth face sheets are finished with a high-gloss two-part aliphatic polyurethane, or acrylic primer only.
- Pebble grain and sandstone-textured face sheets are through-colored and can also be painted a custom color.
- Achieve the rich look of real stained wood with our selection of natural wood stain colors, or paint any color. Rustic wood grain face sheets feature authentic oak species wood grain replication, and contemporary wood grain face sheets feature authentic cherry species wood grain replication.
- Fire-rated mineral core with edge blocking for superior screw holding
- Stainless steel vision lites provided by Special-Lite or others
- Size restrictions vary by model, see configuration worksheet for details



AF-FR Series Fire Door & Frame Models

Door Model	Face Sheet
AF-200FR	Smooth
AF-217FR	Pebble Grain FRP
AF-219FR	Rustic Wood Grain FRP
AF-219-1FR	Contemporary Wood Grain FRP
AF-220FR	Sandstone-textured FRP

Frame Model	Wall	Depth	Face	Head
FR Series Pultruded Framing	1/4"	5-3/4" and 6-3/4" (immediate door frame only)	2"	2" or 4"

Fire-Rated Framing

Pultruded fire-rated framing with a depth of 5-3/4" or 6-3/4" with 2" or 4" heads is available to provide a complete door system for industrial locations requiring fire-rated doors and frames. AF-FR Series Doors and Frames are covered by a 10-year parts and labor warranty.