




HURRICANE

Single No Lite SL-16, 16SS, 17, 18, 19, 20

CONFIGURATION WORKSHEET

Model: SL--9875-S-NL---
base door model hardware set framing op. hardware

FL#: 9875_R4



Swing: Outswing
Outside HVHZ: Yes
Inside HVHZ: No
Water Infiltration: No
Max Overall Size: 46" x 92" Single Door (Including Frame)
Glazing: NONE

Choose Required Hardware Set:

Hardware Set 1 (Design Pressure +60 / -53 psf)		
QTY	Part #	Description
1	SL-11HD	Select Products Continuous Hinge
1	8701	Adams Rite Rim Exit Device
1	SL-86	Special-Lite Recessed Pull
1	950N	National Guard Products Threshold

Hardware Set 2 (Design Pressure ±70 psf)		
QTY	Part #	Description
1	SL-11HD	Select Products Continuous Hinge
1	D53LD	Schlage Cylindrical Lockset
1	10-025	Schlage Standard Strike
1	950N	National Guard Products Threshold

Hardware Set 3 (Design Pressure ±70 psf)		
QTY	Part #	Description
1	SL-11HD	Select Products Continuous Hinge
1	L9453P	Schlage Mortise Lockset
1	30-021	Schlage Mortise Cylinder
1	10-072	Schlage 4-7/8" Strike
1	950N	National Guard Products Threshold

Choose a Framing Option:

Framing Options	
NO.	Description
F0	Approved Framing by Others
F1	1" x 4-1/2" Aluminum Tube Frame by Special-Lite
F2	2" x 4-1/2" Aluminum Tube Frame by Special-Lite
F3	2" x 6" Aluminum Tube Frame by Special-Lite
F4	SL-70 Insert Frame with or without Capping by Special-Lite Installed Over Approved Framing by Others

Choose Optional Hardware:

Optional Hardware	
NO.	Description
NA	No Optional Hardware
PR	Special-Lite Concealed Prox Reader Prep
TR	Special-Lite 7" Aluminum Threshold
OP	Any Pull or Trim other than SL-86
CL	Any Closer