



BULLET RESISTANT

Single Swing and Standard Pairs AF-200BR³

CONFIGURATION WORKSHEET

Model: AF-200BR³--
single/pair glass

Custom Vision Lite Size or Multiple Lite Size (D.L.O.): x x
width height quantity

| PRODUCT LIMITATIONS | |
|----------------------|--|
| Rating: | UL-752 Level 3 NIJ-STD-0108.01 Level 3A |
| Max Size: | 48 in. x 96 in. Single Door (Max D.O.) 96 in. x 96 in. Double Door (Max D.O.) |
| Vision Lites: | AF-BR ³ LK |

| Glazing Options | |
|-----------------|-------------------|
| Code | Description |
| LTI | LTI Smartgard BR3 |
| BR | Hygard BR1250 |
| EX | Hygard EX1300 |

Product Description:

Pultruded FRP stile and rail construction with mitered corners, ARMOR CORE UL-752 Level 3 panel mortised into stiles and rails, surrounded with polypropylene honeycomb panels with factory bonded face sheets for durability. Smooth face sheets are primed and ready for field painting or can be painted with any of our 10 standard high gloss colors. Door edges and FRP lite kits are painted to match face sheet color.

Design Guidelines:

- Vision Lite Sizes (based on 3'0" x 7'0" door):
 - 12" x 12"
 - 21-1/2" x 32" Half Lite
 - 17-1/2" x 63" Full Lite
 - 4" x 25" Narrow Lite
 - 21-1/2" x 32" (top) 21-1/2" x 24" (bottom) Double Half Lite
- Compatible with most ballistic hardware.
- Not compatible with SL-301.
- Not compatible with CVR type hardware.
- No electric wire raceways.
- Hinge clearance not to exceed 3/8".
- Choice of 10 standard high-gloss colors, custom colors, or primer only.
- Only standard knob and mortise lock hardware preps will be done at factory.
- Standard 3-sided frames only unless submitted to Special-Lite for Customization Review and Denial/ Approval. (Please allow 7-10 days for the review process.)
- RATINGS ONLY MAINTAINED WHEN INSTALLED IN AF-150BR³ FRAMING.