



BULLET RESISTANT

Single Swing and Standard Pairs AF-219-1BR³

CONFIGURATION WORKSHEET

Model: AF-219-1BR³--
single/pair glass

Custom Vision Lite Size or Multiple Lite Size (D.L.O.): x x
width height quantity

PRODUCT LIMITATIONS	
Rating:	UL-752 Level 3 NIJ-STD-0108.01 Level 3A
Max Size:	48 in. x 96 in. Single Door (Max D.O.) 96 in. x 96 in. Double Door (Max D.O.)
Vision Lites:	AF-BR ³ LK

Glazing Options	
Code	Description
LTI	LTI Smartgard BR3
BR	Hygard BR1250
EX	Hygard EX1300

Product Description:

Pultruded FRP stile and rail construction with mitered corners, ARMOR CORE UL-752 Level 3 panel mortised into stiles and rails, surrounded with polypropylene honeycomb panels with factory bonded face sheets for durability. Contemporary wood grain face sheet and a variety of stain, painted and custom colors available. Door edges and FRP lite kits are painted to match face sheet color.

Design Guidelines:

- Vision Lite Sizes (based on 3'0" x 7'0" door):
 - 12" x 12"
 - 21-1/2" x 32" Half Lite
 - 17-1/2" x 63" Full Lite
 - 4" x 25" Narrow Lite
 - 21-1/2" x 32" (top) 21-1/2" x 24" (bottom) Double Half Lite
- Compatible with most ballistic hardware.
- Not compatible with SL-301.
- Not compatible with CVR type hardware.
- No electric wire raceways.
- Hinge clearance not to exceed 3/8".
- Choice of 10 standard high-gloss colors, custom colors, or primer only.
- Only standard knob and mortise lock hardware preps will be done at factory.
- Standard 3-sided frames only unless submitted to Special-Lite for Customization Review and Denial/ Approval. (Please allow 7-10 days for the review process.)
- RATINGS ONLY MAINTAINED WHEN INSTALLED IN AF-150BR³ FRAMING.