Special-Lite®

## Monumental Stile & Rail Door Estimate/Order Form

Job Name REQUIRED in order to process: \_\_\_\_\_

Please download to your desktop prior to filling in your order information. Forms filled out via web browser will download blank.

	SL-14 (Med. Stile)SL-15 (Wide Stile)Door(s) & Frame(s)Door(s) onlyFrame(s) only									
1.	Door Mark (I.D.):									
2.	Handing: Single Pairs Unequal Pair (Specify quantity of single/pairs of doors required. All doors on each sheet must be identical. Use separate sheets for doors with differences									
	Interior   LHRB   Quantity:     RHRB   Quantity:     Interior   Quantity:     Interior   Quantity:     RHRB   Quantity:     Quantity:     Quantity:     Quantity:     Interior     Quantity:     Quantity:     Quantity:     Quantity:     Interior     Quantity:     Quantity:     Interior     Quantity:         Interior     Quantity:									
3.	Opening Dimensions: (max size= 144" x 144")         (Measure opening to finished floor. For both width and height, measure opening at several points and record the smallest dimension.)         Width:       Height:       Thres. Height:       (default bottom undercut: 3/4"									
	Width:       Height:       Thres. Height:       (default bottom undercut: 3/4"         Rough Opening (masonry)       Door Opening (jamb to jamb)       Net Door Size       Net Frame Size (outside tip to tip of new frame)									
4.	Swing: Degree of Door Opening°									
5.	Aluminum Finish: (Special anodizing or painting will result in additional lead time.)         Clear (stock)       Dark Bronze (stock)       Black       Champagne         Light Bronze       Medium Bronze       Painted: (enter color)									
6.	Bottom Rail: 6-1/2" Standard 10" (ADA) Double Stacked (up to 13")									
7.	Mid-Rail/Panel:       2-1/2" Mid-Rail       4" Mid-Rail       6-1/2" Mid-Rail       8" Mid-Rail         None       12" Mid-Panel (SL-484)									
8.	Mid-Panel Face Material: (if applicable)       Ext       Int       Aluminum*       Ext       Int       FRP Pebblegrain       Ext       Int         Image:									
	AMIP WOOdgrain Face sheet Color/Texture: (refer to color charts) *Unless specified differently, aluminum mid-panel faces will match the finish selected in section 5 above.									
9.	<b>Door Infill:</b> By Special-Lite By Others *Please send elevation and/or configuration of muntins if needed. Provide any further instruction at end of form.									
Glass 1/4" Polycarbonate 1/4" Tempered (Clear) 1/4" Laminated (Clear) 1" Tempered (Clear) 0										
	S-Label       1" IGU       Fire-Rated Glazing       Glass Thickness:       1/4"       1"									
	Louver Louver Louver with screen									
	Muntins 1" Glass w/Int. Muntins* 1/4" Glass w/alum. Surface Applied Muntins* (1/2" or 1-1/4" width)									
	Panel 1" Panel (specify face sheet) 1/4" Panel (specify face sheet)									
10.	Framing: By Special-Lite By Others No Framing Unless specified, existing door stop is assumed to be 5/8" high.									
	Frames Options:  Perimeter  Complicated									

Provide any existing hardware locations to match. Please include a separate elevation for any frame more complicated than a perimeter frame.

	Door Mark (I.D.):								
10.	Framing (continued):								
	Frame Glass Thickness:								
	Provide glass thickness for transom/side lite. Glass not supplied by Special-Lite for framing.								
	Frame Panels:   By Special-Lite   By Others								
	□ 1/4" □ 1" □ 1-3/4"								
	Heavy Wall Tube Frames with Applied Stop :								
	5/8" x 4-1/2" 1" x 4-1/2" 1" x 6"								
	2" x 4" 2" x 4-1/2" 2" x 5" 2" x 6"								
	□ 1-3/4" x 4" □ 1-3/4" x 4-1/2" □ 1-3/4 x 5" □ 1-3/4" x 6"								
	Thermally Broken Frames:2" x 4-1/2"2" x 6"								
	Heavy Wall Flush Glazed Frames: 1-3/4" x 4-1/2" 2" x 4-1/2" 2" x 6"								
	Retrofit Framing :       Insert Frame       Insert Frame & Capping       Capping (Frame Detail Required)         (Complete Insert Frame w/ or w/o Capping Measuring Instruction Sheet if order includes capping)								
11.	Continuous Hinge by Special-Lite: Yes No Choose Model: SL11HD A110 HD								
12.	Adjustable Bottom Brush by Special-Lite: (SL-301 - Not available for use with concealed vertical rods.)								
13.	Adjustable Astragal by Special-Lite: (AS-4A) with optional radius meeting stile 🗌 Yes 📄 No								
14.	Smoke Rating (SL-15 ONLY):       Yes       No       MAXIMUM SIZE: Single Swing: 48" x 120"       Pairs: 96" x 120"         REQUIRED GLAZING: 1" IGU (tested ) or any listed fire glazing								

15. Hardware: (Surface closers and surface holder/stops are field prepped and installed. The default strike centerline is 40 - 5/16" from floor.)

If sending hardware for application, when will it arrve at Special-Lite? DATE: Quantity Manufacturer Item# Size Finish						Prep per Will be Temp. <u>Sent to SL</u>	
Quantity	Manufacturer	Item#	5120	FIIIISII	by SL		

15. Special Instructions: (If your order has specific performance requirements to meet, please note it here.)