



BULLET RESISTANT

Single Swing and Standard Pairs AF-200BR3, AF-217BR3, AF-219BR3, AF-219-1BR3, AF-220BR3

CONFIGURATION WORKSHEET

Model: AF- BR3- - -
model single/pair glass

Custom Vision Lite Size or Multiple Lite Size (D.L.O.): X X
width height quantity

PRODUCT LIMITATIONS

Rating: UL-752 Level 3
NIJ-STD-0108.01 Level 3A

Max Size: 48 in. x 96 in. Single Door (Max D.O.)
96 in. x 96 in. Double Door (Max D.O.)

Vision Lites: AF-BR³LK

Glazing Options

Code	Description
LTI	LTI Smartgard BR3 Glass Clad Polycarbonate
BR	Palshield UL3-1250 Polycarbonate

Product Description:

Pultruded FRP stile and rail construction with mitered corners, ARMOR CORE UL-752 Level 3 panel mortised into stiles and rails, surrounded with polypropylene honeycomb panels with factory bonded face sheets for durability. FRP vision lite kits are painted to match the face sheet color. Stainless Steel edge capping is screw-applied, welded, and buffed at the corners.

Design Guidelines:

- Vision Lite Sizes (based on 3'0" x 7'0" door):
 - 12" x 12"
 - 21-1/2" x 32" Half Lite
 - 17-1/2" x 63" Full Lite
 - 4" x 25" Narrow Lite
 - 21-1/2" x 32" (top) 21-1/2" x 24" (bottom) Double Half Lite
- Compatible with most ballistic hardware.
- Not compatible with SL-301.
- Not compatible with CVR type hardware.
- No electric wire raceways.
- Hinge clearance not to exceed 3/8".
- Only standard knob and mortise lock hardware preps will be done at factory.
- Standard 3-sided frames only unless submitted to Special-Lite for Customization Review and Denial/ Approval. (Please allow 7-10 days for the review process.)
- RATINGS ONLY MAINTAINED WHEN INSTALLED IN AF-150BR3 FRAMING.