

SL-16 Door & Frame Estimate/Order Form

Job Name REQUIRED in order to process: _______
Please download to your desktop prior to filling in your order information. Forms filled out via web browser will download blank.

	Door(s) & Frame(s)	Door(s) only	Frame(s) only	Job Bid Date:	
1.	Door Mark (I.D.):				
2.	Handing: Sing	gle P	Pairs Unequal Pair	(Specify quantity of single/pairs of doors no sheet must be identical. Use separate sheet	
	LH Quantity: RH	Quantity: (check a	Quantity:	Height - measured fror finished floor t the underside	:0
	LHRB RHRB	Quantity:	Quantity:	<u> </u>	
3.	Opening Dimensions: (SL-16 to (Measure opening to finished floor. For both w		several points and record the smallest	Opening Threshold Width Height	Opening Width
	Width:	_		eight: (defaul	
	Rough Opening (masonry t	o masonry) Door Oper	ning (jamb to jamb) Net Do	oor Size Net Frame Size	outside tip to tip of new frame)
4.	Swing: Degree of Door Opening	og°			
5.	Aluminum Finish: (Special anodi	zing or painting will result in addition	al lead time. Finish selected here will	apply to doors, frames and aluminum vision kit	s.)
	Clear (stock) Medium Bronze	(,	Black Cr	nampagne Light Bronze	
6.	Aluminum Facesheet:	Entibosoca	Ext Int .062" Smooth etch/detail and/or further instruction	Ext Int	t] Fluted
7.	Vision Lite: Yes No	FL Series is standard. Optio	ns: FL-LPBev Lite K	it FL-SecureLite 1/2" bite	FL-Securelite 1" bite
	12" x 12" H	alf Lite	Full Lite	Narrow Lite	
	Double Lite A	luminum Surface Muntin	IS* (1/2" or 1-1/4" width)	Other* (provide sketch)	
8.	Glass/Louvers: By Sp	ecial-Lite By Others	None *If needed plea	ase clarify with sketch/detail and/or further inst	ruction at end of form.
	1/4" Polycarbonate	1/4" Tempered (Clear)	1/4" Laminated (Clear	1" Tempered (Clear)	Other* (provide thickness & detail)
	Louver Lou	iver with screen 1"	Panel (specify face sheet)	1/4" Panel (specify face sheet) 1"	w/Internal Muntins*
9.	Framing: B	y Special-Lite By Oth	ners No Framing	Unless specified, existing door stop is assu	med to be 5/8" high.
	Frames Options: Provide any existing hardware local	-	licated arate elevation for any frame more con	mplicated than a perimeter frame.	
	Frame Glass Thickr	ness: 1/4" n/side lite. Glass not supplied by Spec	1" cial-Lite for framing.		

	9.	Framing (continued):		Door Mark (I.D.):						
Sign x 4-1/2"		Fra	me Panels:	By Special-Lite	By Others					
S/8" x 4-1/2"				1/4"	1"	1-3/4"				
2" x 4" 2" x 4-1/2" 2" x 5" 2" x 6" 2" x 8" 1-3/4" x 4" 1-3/4" x 4-1/2" 1-3/4 x 5" 1-3/4" x 6" Thermally Broken Frames: 1-3/4" x 4-1/2" 2" x 6" Heavy Wall Flush Glazed Frames: 1-3/4" x 4-1/2" 2" x 4-1/2" 2" x 6" Retrofit Framing: Insert Frame Insert Frame & Capping Capping (Frame Detail Resulted Controlled Scapping) 10. Continuous Hinge by Special-Lite: Yes No Chome Muslet SL11HD A110 HD 11. Adjustable Bottom Brush by Special-Lite: (AS-AA) with optional radius meeting size Yes No 12. Adjustable Astragal by Special-Lite: (AS-AA) with optional radius meeting size Yes No 13. Hardware: (Surface Coers and surface holder/stops are field prepped and installed. The default strike centerline is 40 - 5/16" from floor.) If sending hardware for application, when will it arrive at Special-Lite? DATE: Size Finish by St. Temps St. Temps St. Supplied by St. Temps St. St. Temps		Неа	ıvy Wall Tube Fra	mes with Applied S	Stop :					
1-3/4" x 4" 1-3/4" x 4-1/2" 1-3/4 x 5" 1-3/4" x 6" Thermally Broken Frames: 2" x 4-1/2" 2" x 6" Heavy Wall Flush Glazed Frames: 1-3/4" x 4-1/2" 2" x 4-1/2" 2" x 6" Retrofit Framing: Insert Frame Insert Frame & Capping Capping grame Detail Required (Complete Insert Frame & Capping Measuring Instruction Sheet if order includes capping) 10. Continuous Hinge by Special-Lite: Yes No Choose Modele SL11HD A110 HD 11. Adjustable Bottom Brush by Special-Lite: (SL-301 - Not available for use with concasid vertical rods). Yes No 12. Adjustable Astragal by Special-Lite: (AS-AA) with optional roduse meeting stile Yes No 13. Hardware: (Surface closers and surface holder/stops are field prepped and installed. The default strike centerline is 40 - 5/16" from floor.) If sending hardware for application, when will it arrive at Special-Lite? DATE: Size Finish by SL Temp. SL Quantity Manufacturer Item# Size Finish by SL Quantity Manufacturer Item# Size Finish Dy SL Quantity Manufacturer Item# On Description of Description Descript				5/8" x 4-1/2"	1" x 4-1/2"	1" x 6"				
Heavy Wall Flush Glazed Frames: 1-3/4" x 4-1/2" 2" x 4-1/2" 2" x 4-1/2" 2" x 6" Retrofit Framing: Insert Frame (Complete Insert Frame & Capping (Complete Insert Frame & Capping (Frame Detail Required) (Complete Insert Frame & Capping (Frame Detail Required) (Complete Insert Frame & Capping & Capping (Frame Detail Required) (Complete Insert Frame & Capping & Capping (Frame Detail Required) (Complete Insert Frame & Capping & Capping (Frame Detail Required) (Complete Insert Frame & Capping & Capping (Frame Detail Required) (Complete Insert Frame & Capping & Capping (Frame Detail Required) (Complete Insert Frame & Capping & Capping (Frame Detail Required) (Complete Insert Frame & Capping & Capping (Frame Detail Required) (Complete Insert Frame & Capping & Capping (Frame Detail Required) (Complete Insert Frame & Capping Measuring Insert Frame & No 12. Adjustable Bottom Brush by Special-Lite: (St-301 - Not available for use with concealed vertical rods.) Yes No 13. Hardware: (Surface cooses and surface hobler/stops are field prepped and installed. The default atrile centerline is 40 - 5/16' from floor.) Prep Will per Supplied			2" x 4"	2" x 4-1/2"	2" x 5"	2" x 6"	2" x 8"			
Heavy Wall Flush Glazed Frames: 1-3/4" x 4-1/2" 2" x 4-1/2" 2" x 6" Retrofit Framing: Insert Frame Insert Frame & Capping Capping Frame Detail Required; Complete Insert Frame w/ or w/o Capping Measuring Instruction Sheet if order includes capping) 10. Continuous Hinge by Special-Lite: Yes No Choose Model: SL11HD A110 HD 11. Adjustable Bottom Brush by Special-Lite: (SL-301 - Not available for use with concealed vertical rocks) Yes No 12. Adjustable Astragal by Special-Lite: (AS-4A) with optional radius meeting stile Yes No 13. Hardware: (Surface closers and surface holder/stops are field preposed and installed. The default strike centerline is 40 - 5/16" from floor) If sending hardware for application, when will it arrive at Special-Lite? DATE: Size Finish by SL Entry Temp. SL Quantity Manufacturer Item# Size Finish by SL Entry SL Entry SL Entry Entry SL			1-3/4" x 4"	1-3/4" x 4-1/2"	1-3/4 x 5"	1-3/4" x 6"				
Retrofit Framing: Insert Frame Insert Frame & Capping Capping (Frame Detail Required) (Complete Insert Frame w/ or w/o Capping Measuring Instruction Sheet if order includes capping) 10. Continuous Hinge by Special-Lite: Yes No Choose Model: SL11HD A110 HD 11. Adjustable Bottom Brush by Special-Lite: (SE-301 - Not available for use with concealed vertical rods.) Yes No 12. Adjustable Astragal by Special-Lite: (AS-4A) with optional radius meeting stile Yes No 13. Hardware: (Surface closers and surface holder/stops are field prepped and installed. The default strike centerline is 40 - 5/16' from floor.) If sending hardware for application, when will it arrive at Special-Lite? DATE: Quantity Manufacturer Item# Size Finish by SL Temp. SL Temp. SL Temp. SL Temp. SL Temp. SL Temp. SL		The	ermally Broken Fr	ames:	2" x 4-1/2"	2" x 6"				
Retrofit Framing: Insert Frame Insert Frame & Capping Capping (Frame Detail Required) (Complete Insert Frame w/ or w/o Capping Measuring Instruction Sheet if order includes capping) 10. Continuous Hinge by Special-Lite: Yes No Choose Model: SL11HD A110 HD 11. Adjustable Bottom Brush by Special-Lite: (SE-301 - Not available for use with concealed vertical rods.) Yes No 12. Adjustable Astragal by Special-Lite: (AS-4A) with optional radius meeting stile Yes No 13. Hardware: (Surface closers and surface holder/stops are field prepped and installed. The default strike centerline is 40 - 5/16' from floor.) If sending hardware for application, when will it arrive at Special-Lite? DATE: Quantity Manufacturer Item# Size Finish by SL Temp. SL Temp. SL Temp. SL Temp. SL Temp. SL Temp. SL		Неа	ıvv Wall Flush Gla	zed Frames:						
10. Continuous Hinge by Special-Lite: Yes No Choose Model: SL11HD A110 HD 11. Adjustable Bottom Brush by Special-Lite: (SL:301 - Not available for use with concealed vertical rods.) Yes No 12. Adjustable Astragal by Special-Lite: (AS-4A) with optional radius meeting stile Yes No 13. Hardware: (Surface closers and surface holder/stops are field prepped and installed. The default strike centerline is 40 - 5/16" from floor.) If sending hardware for application, when will it arrive at Special-Lite? DATE:			,		2" x 4-1/2"	2" x 6"				
11. Adjustable Bottom Brush by Special-Lite: (st-301 - Not available for use with concealed vertical rods.) 12. Adjustable Astragal by Special-Lite: (AS-4A) with optional radius meeting stile 13. Hardware: (Surface closers and surface holder/stops are field prepped and installed. The default strike centerline is 40 - 5/16* from floor.) If sending hardware for application, when will it arrve at Special-Lite? DATE: Quantity Manufacturer Item# Size Finish by SL Temp. SL		Ret	rofit Framing :							
13. Hardware: (Surface closers and surface holder/stops are field prepped and installed. The default strike centerline is 40 - 5/16* from floor.) If sending hardware for application, when will it arrive at Special-Lite? DATE: Quantity Manufacturer Item# Size Finish Supplied by SL ———————————————————————————————————	10.	Continuou	s Hinge by Special	l -Lite: Yes N	No Choose Model: SI	L11HD A11	0 HD			
13. Hardware: (Surface closers and surface holder/stops are field prepped and installed. The default strike centerline is 40 - 5/16* from floor.) If sending hardware for application, when will it arrive at Special-Lite? DATE: Quantity Manufacturer Item# Size Finish Supplied by SL ———————————————————————————————————	11.	Adjustable	Bottom Brush by	Special-Lite: (SL-301	- Not available for use with con	cealed vertical rods.)	Yes	No		
13. Hardware: (Surface closers and surface holder/stops are field prepped and installed. The default strike centerline is 40 - 5/16* from floor.) If sending hardware for application, when will it arrive at Special-Lite? DATE: Quantity Manufacturer Item# Size Finish			-	_						
If sending hardware for application, when will it arrive at Special-Lite? DATE: Quantity Manufacturer Item# Size Finish Supplied by SL Temp. SL ———————————————————————————————————	14.	Aujustable	Astragar by Speci	lai-Lite. (AS-4A) with optic	nai radius meeting stile	103 100				
	13.	If sending hard	ware for application, wher		? DATE:			Supplied	per	Will b Sent to
	Quar	ntity Ma	anufacturer	Item#		Size	Finish			
								_		
								$\perp \square$		
								$+ \square$		
								 	ᆜ	
								+	 	
								+-=	屵	
								_	_Ц	
14. Special Instructions: (If your order has specific performance requirements to meet, please note it here.)										