



SL-20 Door & Frame Estimate/Order Form

Job Name REQUIRED in order to process: _____

Please download to your desktop prior to filling in your order information. Forms filled out via web browser will download blank.

Door(s) & Frame(s)	Door(s) only	Frame(s) only	Job Bid Date: _____
-------------------------------	---------------------	----------------------	----------------------------

1. **Door Mark (I.D.):** _____

2. **Handing:**

Single	Pairs	Unequal Pair	
LH Interior Quantity: _____	RH Interior Quantity: _____	Interior (check active leaf) Interior Quantity: _____	(Specify quantity of single/pairs of doors required. All doors on each sheet must be identical. Use separate sheets for doors with differences.)
LHRB Interior Quantity: _____	RHRB Interior Quantity: _____	Interior Quantity: _____	

3. **Opening Dimensions:** (SL-20 max size is 48" x 96")
 (Measure opening to finished floor. For both width and height, measure opening at several points and record the smallest dimension.)

Width: _____ Height: _____ Thres. Height: _____ (default bottom undercut: 3/4")

Rough Opening (masonry to masonry) Door Opening (jamb to jamb) Net Door Size Net Frame Size (outside tip to tip of new frame)

4. **Swing:** Degree of Door Opening _____ °

5. **Aluminum Finish:** (Special anodizing or painting will result in additional lead time. Finish selected here will apply to doors, frames and aluminum vision kits.)

- | | | | | |
|---------------|------------------------------|-------|-----------|--------------|
| Clear (stock) | Dark Bronze (stock) | Black | Champagne | Light Bronze |
| Medium Bronze | Painted: (enter color) _____ | | | |

6. **FRP Sandstone-Textured Facesheet Color:**

- | | | | | |
|-----------------------------|---------------|------------------------|--------------------|---------------------|
| Ext Int White | Ext Int Beige | Ext Int Hartford Green | Ext Int Light Grey | Ext Int Dark Bronze |
| Military Blue | Brick Red | Seawolf | Sage Brown | |
| Painted: (enter code) _____ | | | | |

*If needed please clarify with sketch/detail and/or further instruction at end of form.

7. **Vision Lite:** Yes No FL Series is standard.

Options: FL-LPBev Lite Kit	FL-SecureLite 1/2" bite	FL-SecureLite 1" bite	
12" x 12"	Half Lite	Full Lite	Narrow Lite
Double Lite	Aluminum Surface Muntins* (1/2" or 1-1/4" width)		Other* (provide sketch)

8. **Glass/Louvers:** By Special-Lite By Others None *If needed please clarify with sketch/detail and/or further instruction at end of form.

- | | | | | |
|--------------------|-----------------------|-------------------------------|---------------------------------|-------------------------------------|
| 1/4" Polycarbonate | 1/4" Tempered (Clear) | 1/4" Laminated (Clear) | 1" Tempered (Clear) | Other* (provide thickness & detail) |
| Louver | Louver with screen | 1" Panel (specify face sheet) | 1/4" Panel (specify face sheet) | 1" w/Internal Muntins* |

9. **Framing:** By Special-Lite By Others No Framing Unless specified, existing door stop is assumed to be 5/8" high.

Frames Options: Perimeter Complicated

Provide any existing hardware locations to match. Please include a separate elevation for any frame more complicated than a perimeter frame.

Frame Glass Thickness: 1/4" 1"

Provide glass thickness for transom/side lite. Glass not supplied by Special-Lite for framing.

9. Framing (continued):

Door Mark (I.D.): _____

Frame Panels:	By Special-Lite	By Others		
	1/4"	1"	1-3/4"	
Heavy Wall Tube Frames with Applied Stop :				
	5/8" x 4-1/2"	1" x 4-1/2"	1" x 6"	
2" x 4"	2" x 4-1/2"	2" x 5"	2" x 6"	2" x 8"
1-3/4" x 4"	1-3/4" x 4-1/2"	1-3/4 x 5"	1-3/4" x 6"	
Thermally Broken Frames:	2" x 4-1/2"	2" x 6"		
Heavy Wall Flush Glazed Frames:				
	1-3/4" x 4-1/2"	2" x 4-1/2"	2" x 6"	

Retrofit Framing :

Insert Frame Insert Frame & Capping Capping (Frame Detail Required)
 (Complete Insert Frame w/ or w/o Capping Measuring Instruction Sheet if order includes capping)

10. Continuous Hinge by Special-Lite: Yes No Choose Model: SL11HD A110 HD
11. Adjustable Bottom Brush by Special-Lite: (SL-301 - Not available for use with concealed vertical rods.) Yes No
12. Adjustable Astragal by Special-Lite: (AS-4A) with optional radius meeting stile Yes No

13. Hardware: (Surface closers and surface holder/stops are field prepped and installed. The default strike centerline is 40 - 5/16" from floor.)

If sending hardware for application, when will it arrive at Special-Lite? DATE: _____

Quantity	Manufacturer	Item#	Size	Finish	Reinforce Only	Supplied by SL	Prep per Temp.	Will be Sent to SL

14. Special Instructions: (If your order has specific performance requirements to meet, please note it here.)