



# SL-20FR Fire-Rated Door Estimate/Order Form

**Job Name REQUIRED in order to process:** \_\_\_\_\_

Please download to your desktop prior to filling in your order information. Forms filled out via web browser will download blank.

<b>Door(s) &amp; Frame(s)</b>	<b>Door(s) only</b>	<b>Frame(s) only</b>	<b>Job Bid Date:</b> _____
-------------------------------	---------------------	----------------------	----------------------------

1. **Door Mark (I.D.):** \_\_\_\_\_ **Building Type:** \_\_\_\_\_

2. **Handing:**

Single	Pairs	Unequal Pair	
LH  Interior Quantity: _____	RH  Interior Quantity: _____	Interior (check active leaf) Quantity: _____	(Specify quantity of single/pairs of doors required. All doors on each sheet must be identical. Use separate sheets for doors with differences.) 
LHRB  Interior Quantity: _____	RHRB  Interior Quantity: _____	Interior Quantity: _____	

3. **Opening Dimensions:** (SL-23 max size: is 48" x 96")  
 (Measure opening to finished floor. For both width and height, measure opening at several points and record the smallest dimension.)

Width: \_\_\_\_\_ Height: \_\_\_\_\_ Thres. Height: \_\_\_\_\_ (default bottom undercut: 3/4")

Rough Opening (masonry to masonry)    Door Opening (jamb to jamb)    Net Door Size    Net Frame Size (outside tip to tip of new frame)

4. **Swing:** Degree of Door Opening \_\_\_\_\_°

5. **Edge Capping Finish:** Stainless Steel

6. **FRP Facesheet:** Sandstone-Textured FRP

Ext Int	Ext Int	Ext Int	Ext Int	Ext Int
White	Beige	Hartford Green	Light Grey	Dark Bronze
Military Blue	Brick Red	Seawolf	Sage Brown	Slate Grey

Painted: (enter code) \_\_\_\_\_

7. **Stainless Steel Vision Lite:** Yes No  
 max. DLO = 704 sq. in.  
 4" x 25"    6" x 28"    10" x 10"    20" x 28"

8. **Glass:** By Special-Lite By Others None  
 3/16" FireLite Standard NT (ceramic)    Other: \_\_\_\_\_

9. **Fire-Rated Framing:** (immediate door frame only)  
 Unless specified, existing door stop is assumed to be 5/8" high.

	By Special-Lite	By Others	No Framing
	Fiberglass Framing by Special-Lite rated for 45 minutes only		
<b>1030 Insert Frame &amp; Capping:</b> Please include sketch of frame detail for capping configuration. (Complete Insert Frame w/ or w/o Capping Measuring Instruction Sheet if order includes capping)	Dark Bronze	Black	Clear
<b>Hollow Metal Frame:</b> (primed only)	Painted: _____		

10. **Label:** (Check one)    30 minute    45 minute    60 minute    90 minute

11. **Continuous Hinge by Special-Lite:** (SL- 11 HD)

Door Mark (I.D.): \_\_\_\_\_

**12. Hardware:** (Surface closers and surface holder/stops are field prepped and installed. The default strike centerline is 40 - 5/16" from floor.)  
4-point latching on all 90-minute pairs, 3-point latching on 20 to 60 minute pairs

If sending hardware for application, when will it arrive at Special-Lite? DATE: \_\_\_\_\_

Quantity	Manufacturer	Item#	Size	Finish	Supplied by SL	Prep per Temp.	Will be Sent to SL

**13. Special Instructions:** (enter below)