



SL/Aluminum Frame Estimate/Order Form

Job Name REQUIRED in order to process: _____

Please download to your desktop prior to filling in your order information. Forms filled out via web browser will download blank.

☐ **Door(s) & Frame(s)**

☐ **Frame(s) only**

Job Bid Date: _____

1. Door Mark (I.D.): _____

Opening Dimensions:

IF FRAME ONLY: Please Enter Rough Opening Size (masonry to masonry)	<div style="border: 1px solid black; width: 60px; height: 20px; margin: 0 auto;"></div> width	X	<div style="border: 1px solid black; width: 60px; height: 20px; margin: 0 auto;"></div> height
--	---	---	--

* For both width and height, measure opening at several points and record the smallest dimension.

2. Handing:

<input type="checkbox"/> Single	<input type="checkbox"/> Pairs	<input type="checkbox"/> Unequal Pair
---------------------------------	--------------------------------	---------------------------------------

<div style="text-align: center;"> LH <input type="checkbox"/> Quantity: _____</div> <div style="text-align: center;"> LHRB <input type="checkbox"/> Quantity: _____</div>	<div style="text-align: center;"> RH <input type="checkbox"/> Quantity: _____</div> <div style="text-align: center;"> RHRB <input type="checkbox"/> Quantity: _____</div>	<div style="text-align: center;"> (check active leaf) Quantity: _____</div> <div style="text-align: center;"> Quantity: _____</div>
---	---	---

3. Frame Finish:

- ☐ Clear (stock) ☐ Dark Bronze (stock) ☐ Black ☐ Champagne ☐ Light Bronze
☐ Medium Bronze ☐ Painted: (enter code) _____

4. Framing: ☐ By Special-Lite Unless specified, existing door stop is assumed to be 5/8" high.

Frames Options: ☐ Perimeter ☐ Complicated

Provide any existing hardware locations to match. Please include a separate elevation for any frame more complicated than a perimeter frame.

Frame Glass Thickness: ☐ 1/4" ☐ 1"

Provide glass thickness for transom/side lite. Glass not supplied by Special-Lite for framing.

Frame Panels: ☐ By Special-Lite
☐ 1/4" ☐ 1" ☐ 1-3/4"

Heavy Wall Tube Frames with Applied Stop :

- | | | | |
|--|--|--------------------------------------|----------------------------------|
| <input type="checkbox"/> 2" x 4" | <input type="checkbox"/> 5/8" x 4-1/2" | <input type="checkbox"/> 1" x 4-1/2" | <input type="checkbox"/> 1" x 6" |
| <input type="checkbox"/> 1-3/4" x 4" | <input type="checkbox"/> 2" x 4-1/2" | <input type="checkbox"/> 2" x 5" | <input type="checkbox"/> 2" x 6" |
| <input type="checkbox"/> 1-3/4" x 4-1/2" | <input type="checkbox"/> 1-3/4" x 5" | <input type="checkbox"/> 1-3/4" x 6" | |

Thermally Broken Frames: ☐ 2" x 4-1/2" ☐ 2" x 6"

Heavy Wall Flush Glazed Frames:

- ☐ 1-3/4" x 4-1/2" ☐ 2" x 4-1/2" ☐ 2" x 6"

Retrofit Framing :

- ☐ Insert Frame ☐ Insert Frame & Capping ☐ Capping (Frame Detail Required)
(Complete Insert Frame w/ or w/o Capping Measuring Instruction Sheet if order includes capping)

4. **Hardware:** (Surface closers and surface holder/stops are field prepped and installed. The default strike centerline is 40 - 5/16" from floor.)
If sending hardware for application, when will it arrive at Special-Lite? DATE: _____

QuantityManufacturerItem#SizeFinishReinforce OnlySupplied by SLPrep per Temp.Will be Sent to SL

5. **Special Instructions:** (If your order has specific performance requirements to meet, please note it here.)