



LiteSpace® Quote Checklist

Please use this resource to ensure you have all the information listed below. This will allow us to provide an accurate estimate for LiteSpace and Dual Glazed LiteSpace Interior Aluminum Framing Systems.

Send this information and any questions to estimating@special-lite.com.

1 LITESPACE REQUIRED ITEMS

Floor plan drawings and elevation drawings if available

Please indicate where each type of system will go on the floor plan if multiple systems are being used. Complete construction drawings are not necessary.

of Openings

Opening Width(s)

Opening Height(s)

Please note or indicate on drawings any differences in height per opening for knee walls, etc.

System Type

- Swing
- Sliding

System Finish

- Clear Anodized
- Black Anodized
- Other

Door Type

- SLI
 - SLI-12, SLI-14, SLI-15
 - 10" Bottom Rail or Other
 - Glazing by SL or Others

- Wood by Others
- Glass by Others
- Other

Number of Each Door Type

Door Handing

Frame Glass Thickness:

- 1/4"
- 3/8"
- 1/2"

Hardware Prep

- Customer Supplied Hardware
- Special-Lite Supplied Hardware
- Special-Lite Prep For Hardware

Door Glass Thickness:

- 1/4"
- 3/8"
- 1/2"
- 1"
- 1/4" Double

2 DUAL GLAZED ADDITIONAL REQUIREMENTS

Job includes Dual Glazed

Please indicate where each type of system will go on the floor plan if there are multiple systems being used.

Second (inside) Frame Channel Glass Thickness

- 1/4"
- 3/8"
- 1/2"