

AF-200, 217, 219-1, 220 All-Fiberglass Door & Frame Estimate/Order Form Job Name REQUIRED in order to process

	☐ Door(s) & Frame(s	\square Door(s) only		Frame(s)	only					
1.	Door Mark (I.D.):		Building Type:							
2.	Handing: Single		Pairs	Unequal I	Pair		e/pairs of doors required. All doors on cal. Use separate sheets for doors with			
	Interior RI Quantity: RHR Underior RHR Quantity: RHR RHR RHR Comparison RHR Compa	Quantity: (check Ir Quantity:	active leaf	Quantity:			Height Threshold Height Width			
3.	Opening Dimensions: (Max door size for AF-200, 217, 220 = 48" x 96" and AF-219-1 = 42" x 99"). Larger sizes may be available, contact Special-Lite for details.									
	Width:	=			=	(default bottom undercut: 3/				
	☐ Rough Opening	Door Opening (jamb t	o jamb)	☐ Net Doo	r Size	☐ Net Frame Siz	e			
		* For both width and height, measure ope	ening at se	veral points and reco	rd the sn	nallest dimension				
4.	Face Sheet & Color:	AF-200 (Smooth)		Primed only		Color:				
	☐ White	Grey		Clay Tan		Brown	Black			
	Yellow	Orange		Red		Blue	Green			
	AF-217 (Pebblegrain - 12 color choices) AF-220 (Sandstone-Textured - 9 color choices)									
	☐ Beige	Dark Bronze		Dark Grey] White	Beige			
	Light Grey	Black		White		Dark Bronze	Light Grey			
	Sage Brown	Desert Sand (formerly sandstone)		Red		Hartford Green	☐ Military Blue			
	Blue	Hartford Green		Slate Grey		Brick Red	☐ Seawolf			
		Custom Color:	Custom Color:				Sage Brown			
	AF-219-1 (Contemporary Wood Grain - 4 color choices)									
	☐ American Cherry ☐ Dark Cherry ☐		Dark Walnut		Light Maple					
		Custom Color:								
5.	Core Material:	Standard - DEFAULT EPS (Expanded Polystyren	Standard - DEFAULT Optional - ADD EPS (Expanded Polystyrene) Core Polypropylene Honeycomb							
6.	Vision Lite Kit:	Glazing by S-L (up to	Glazing by S-L (up to half lite)			rs None				
	☐ 12" x 12"	☐ Half Lite		Full Lite] Narrow Lite	☐ Double Lite			
	Other (specify):									
7.	Glass Type:	☐ Tempered		Laminated		Other				
8.	Glass Thickness:	<u> </u>		1"						
9.	FRP Louver:	☐ Insect Screen								
	☐ 12" x 12"	☐ 18" x 18"		24" x 18"						
	□ Тор	Bottom	П	Other (specify): _						

		Door Mark (I.D.):								
10.										
	(Paint matches door)				e to verify if framing configuration					
11.	AF-150 FRP Frames: (Paint matches door)	2" Head F	Face 4" Head Face KD I		Velded Frame					
	<u> </u>	7-3/4"	Factory Adjustable	Frame:						
	6-3/4"	☐ 8-3/4"								
12.	a. Anchor Type: AF-150/250 Concrete/Block Anchorage ✓ AF-250 Drywall Anchorage ✓									
	☐ Existing Concrete/Block ☐ Concealed Existing Masonry Anchor ☐ FRP Frame and Metal Studs									
	Punch & Dimple Sill Anchor	☐ New Co	ncrete Block (T anchor)	slock (Tanchor) FRP Frame and Wood Studs						
L	AF-150 Drywall Anchorage									
	Standard Jamb Anchor Tuck Condition Opt. Punch & Dimple TuckMetal Studs									
	☐ KD Wrap Condition ☐ Opt. Punch & Dimple TuckWood Studs									
13.	Threshold (Pultruded FRP by S-L)) None	Choose One Saddle Bumpe	r Non-S	SKID option					
14.	Frame Install Kit: (Tapcon	stainless steel fasteners	and composite frame shims) Yes	□ No						
	FRP "T" Astragal:	Active Door								
10.	Titl Tiblingui.	neave book	I Indedve Door							
16.	Hardware (Field installed): (Prep	per template if applicabl	le)							
Quar	ntity Manufacturer		Item#	Size	Finish					
_										
L										
1 7.	Special Instructions: (If y	our order has specific pe	rformance requirements to meet, please note it here.)							
1										