

FIRE-RATED DOORS & FRAMES

The AF-FR Series All-Fiberglass doors are available with smooth, pebble grain or sandstone-textured face sheets and in 20, 45, 60, and 90 minute fire ratings. Tested in accordance with UBC 7-2, NFPA 252 and UL 10C requirements, the AF-FR Series have passed the 1-1/2 hour positive pressure test, hose stream test, and 250 degree temperature rise tests, and are labeled by Intertek.

Features & Benefits

- Singles or pairs up to 4' x 8' maximum net size per leaf
- Smooth, pebble grain or sandstone-textured FRP door face sheets with smooth door edges
- Smooth face sheets contain high-gloss two-part aliphatic polyurethane finish, or acrylic primer only
- Intumescent tape concealed under door edges for clean appearance
- Fire-rated mineral core with edge blocking for superior screw holding
- Stainless steel vision lites provided by Special-Lite or others
- Smooth door is identical in appearance to AF-100 Series Doors. Painted finish only
- Pebble grain and sandstone-textured face sheets are identical in appearance to AF-200 Series Doors and face sheets are through-colored or painted



AF-FR Series Fire-Rated Door & Frame Models

Door Model	Face Sheet
AF-200FR	Smooth
AF-217FR	Pebble grain FRP
AF-220FR	Sandstone-textured FRP

Frame Model	Wall	Depth	Face	Head
FR Series Pultruded Framing	1/4"	5-3/4" and 6-3/4" (immediate door frame only)	2"	2" or 4"

Fire-Rated Framing

Pultruded fire-rated framing with a depth of 5-3/4" or 6-3/4" with 2" or 4" heads is available to provide a complete door system for industrial locations requiring fire-rated doors and frames. AF-FR Series Doors and Frames are backed by a hassle-free 10-year parts and labor warranty.