

## **AF Composite**AF-200, 217, 219-1, 220

## All-Fiberglass Door & Frame Estimate/Order Form

	☐ Door(s) & Frame(s)	☐ Door(s) only	☐ Frame(s) or	nly				
1.	Door Mark (I.D.): Building Type:							
2.	Handing: Single	□Pa	airs Unequal F	(Specify quantity of single/p each sheet must be identical differences.)	oairs of doors required. All doors on l. Use separate sheets for doors with			
	LHRB RHRB	nterior Int	Quantity:	l Opening l	Height  Threshold Height  Width			
3.	Opening Dimensions: (Ma	x door size for AF-200, 217, 220 =	48" x 96" and AF-219-1 = 42	'	0 1			
	Width:	Height:	Thre	s. Height:	(default bottom undercut: 3/4")			
	Rough Opening  * For both width and height, measure opening	Door Opening (jam		☐ Net Door Size	☐ Net Frame Size			
4.	Face Sheet & Color:  White	Grey	☐ Primed only ☐ Clay Tan	Color: Brown	☐ Black			
	Yellow	Orange	Red	Blue	Green			
	☐ AF-217 (Pebblegrain - 12 color ch ☐ Beige ☐ Light Grey ☐ Sage Brown ☐ Blue	☐ Dark Bronze ☐ Black ☐ Desert Sand ☐ Hartford Green	Dark Grey White Red Slate Grey	☐ White ☐ Dark Bronze ☐ Hartford Green ☐ Brick Red	Beige Light Grey Military Blue Seawolf Sage Brown			
	AF-219-1 (Contemporary Wood							
	American Cherry	_	☐ Dark Walnut					
5.	Core Material:	Standard - DEFAULT  EPS (Expanded Po	olystyrene) Core		tional - ADD Polypropylene Honeycomb			
6.	Vision Lite Kit:  12" x 12"  Other (specify):	Glazing by S-L (up	to half lite)	ing by others	☐ Double Lite			
7.	Glass Type:	☐ Tempered	☐ Laminated	☐ Other				
8.	Glass Thickness:	<b>1/4</b> "	<b>1</b> "					
9.	FRP Louver:  ☐ 12" x 12"  ☐ Top	☐ Insect Screen ☐ 18" x 18" ☐ Bottom	☐ 24" x 18" ☐ Other (specify)	):				

	Door Mark (1.D.):							
10.	AF-250 FRP Frames: 5-3/4" [Paint matches door]	2" Head Face 🔲 4" Head Fac						
11.	AF-150 FRP Frames: 2" Head I	Face	Contact Special-Lite to verifiallows for this option. Addl.  Welded Fram	freight applies				
	□ 5-3/4" □ 7-3/4"	☐ Factory Adjusta	able Frame:					
	☐ 6-3/4" ☐ 8-3/4"	_ , ,						
12.	Anchor Type: AF-150/250 Concrete/	Block Anchorage ▼	AF-250 Drywall Ar	nchorage 🕳				
	☐ Existing Concrete/Block☐ Concealed Existing Masonry Anchor ☐ FRP Frame and Metal Studs							
	Sill Anchor New Concrete Block (Tanchor) FRP Frame and Wood Studs							
г	AF-150 Drywall Anchorage							
	☐ Standard Jamb Anchor Tuck Condition ☐ Opt. Punch & Dimple TuckMetal Studs							
L	☐ KD Wrap Condition ☐ Opt. Punch & Dimple TuckWood Studs							
13.	Threshold (Pultruded FRP by S-L) None	Choose One Saddle Bump	oer Non-SKI	□ Non-SKID option				
1 /	Frame Install Vite		Voc. D No.					
	Frame Install Kit: (Tapcon stainless steel faste		Yes  No					
15.	FRP "T" Astragal:	Door						
16.	$\boldsymbol{Hardware} \text{ (Field installed): (Prep per template if applications)}$	oplicable)						
Qua	ntity Manufacturer	Item#	Size	Finish				
	+							
17.	<b>Special Instructions:</b> (If your order has specific	performance requirements to meet, please note it he	ere.)					
ĺ								